



Becker 100% Oil-Free Rotary Carbon Vane Compressors

Becker oil-free compressors are designed to operate on a continuous duty basis at any pressure level from open flow to 26 PSIG, depending on the series. All Becker oil-free pumps utilize self-lubricating, graphite composite vanes, specifically engineered for Becker Pumps. No oil to change and only minimal maintenance is required. Each pump comes with a built-in inlet filter, pressure relief valve and vibration isolators as standard equipment.

DT Series

Model	Horsepower	CFM @ Open Flow	Max. Pressure (PSIG)	Noise Level (dBa)
DT 4.4	0.24	2.9	15	60.5
DT 4.8	0.6	5.6	15	61.5
DT 4.10	0.6	7.1	15	62
DT 4.16	0.94	11.2	15	64
DT 4.25	1.75	17.6	15	67
DT 4.40	2.95	28	15	70

KDT Series

Model	Horsepower	CFM @ Open Flow	Max. Pressure (PSIG)	Noise Level (dBa)
KDT 3.60	5	37	22	74
KDT 3.80	7.5	45	22	76
KDT 3.100	10	69	22	78
KDT 3.140	12	90	22	84

DTLF Series

Model	Horsepower	CFM @ Open Flow	Max. Pressure (PSIG)	Noise Level (dBa)
DTLF 2.200	12.1	127	22	82
DTLF 2.200	17.7	127	26	83
DTLF 2.250	12.1	172	7.25	80
DTLF 2.250	24.1	172	26	85
DTLF 2.400	17.7	259	13.1	81
DTLF 2.400	29.5	259	26	82
DTLF 2.500	24.1	353	11.6	82
DTLF 2.500	48.3	353	26	82



Features

- 100% oil-free
- Continuous duty rated
- Quiet operation
- Compact design
- Low maintenance

Benefits

- No oil or water
- No cycling times
- No silencer enclosures needed
- Small footprint for space savings
- Field serviceable reduces downtime

Applications

- Soil remediation
- Aeration
- Waste water treatment
- Pneumatic conveying
- Printing

Contact our staff today. We're ready to help. Call 888-633-1083 or email: info@beckerpumps.com.



Nationwide Sales and Service: USA, Canada, and Mexico 888-633-1083

Becker Pumps Corp. • 100 East Ascot Lane • Cuyahoga Falls, Ohio 44223
Tel 330-928-9966 • Fax 330-928-7065 • info@beckerpumps.com • www.beckerpumps.com